

STS Safe-MiniSource



The STS Safe-MiniSource is a simulated radiation source for use with the Safe-Series range of instruments.

The Safe-MiniSource is a fixed activity source with a near isotropic field pattern, its small size makes it easily hidden for carrying out training such as lost source recovery.

The Safe-Variable MiniSource is compatible with the whole Safe-Series range of instruments and can be provided in a range of different activity and isotope characteristics depending on the customers requirements.

Dimensions (mm)	80H	60W	40D
Weight (KG)	0.20KG		
Construction	Moulded Plastic Case		
Controls	1 surface mounted push button	Gloved operable button	
Control Keys	On/Off		
Display Type	None		
Backlight	N/a		
Battery	3 x AAA 1.5V cells	THIS UNIT CANNOT BE MAINS RECHARGED	Battery life 10 hrs+
Emitter	STS radio frequency Detector	3 pole emitter for 360 degree Isotropic field	
Low Battery LED	Green on	Red – Low Battery	
Isotope Library	Fixed single isotope field		
Isotope Activity	Fixed Activity level		
Operating & Storage Temperature	Operating temp 0 to +30C	Storage temp 0C to +40C	
Warm up time	10 seconds from switch on to ready.		
Available Meters	Survey-Safe, FH40G,6150AD	RadEye G10,Epd, Dosisafe	
Additional Information	<p>The STS Safe-MiniSource is not designed to be intrinsically safe and therefore should not be used in hazardous environments. The units are not waterproof and contain delicate and sensitive electronics which may be caused to fail if exposed to moisture. Units should be stored in a clean and dry environment, batteries should be removed if storing for more than 4 weeks.</p> <p>Instrument response will be affected by environmental conditions such as the presence of large reflective surfaces, substantial metal structures and variable wall thicknesses.</p>		

Safe Training Systems Ltd Tel: +44 (0) 1189 799591 Email: sales@safetrainingsystems.com

Web: safetrainingsystems.com Registered in England No.2654899 VAT no. GB572853808